



Hydrapox FL01W

Water Base Epoxy Coating

Description

Hydrapox FL01W is an water base epoxy coating specially use for coating on wall and floor coating.

Advantage

- Environment Friendly
- Good Adhesion to Substrate
- Easy to Clean
- Good Chemical resistance
- Good Durability
- Non-Toxic
- Easy to Apply and Maintain
- Can be mix with cement mortar to use as epoxy-cement patching mortar

Instruction for Use

1. Clean the substrate by remove laitance, oil, grease and dust.
2. Mix the resin with hardener at the ration 1:2 by wt. Stir it 2-3 min. with low speed mixer until homogeneous.
3. Apply by roller or brush.

Packaging

Part A : 1.7 kg. , Part B : 3.3 kg.

Storage

Store in dry place at the room temperature.

Act (Thailand) Co., Ltd.

Address : 19 Moo 1 Kubangluang
Lardlumkaew Pathumthai 12140
Tel. : (66)-0-2979-4446-9 , (66)-0-29794936-9
Fax. : (66)-0-2979-4445
Email : info@actthai.com
Web Site : <http://www.actthai.com>

Characteristic

Density	: 1.05±0.01
Solid Content	: 65 ± 2 %
Mixing Ratio	: 1 / 2 by Wt.
No. of Coat	: 2
Coverage	: 0.2-0.25 kg/ m ²
Thickness ,wet	: 200 - 250 µm.
,dry	: 120 - 160 µm.
Pot Life	: 30 -45 min.
Drying Time	: 3 Hr.
Time to recoat	: 16-24 Hr.

Cleaning

The working equipment, tools etc., can be mechanically cleaned by using brushes in combination with Water. The cleaning should be done immediately after the completion of the work and within the pot life of the material to avoid sediments on the equipments ,tools etc

Precautions

During application observe safety hints on containers as well as local regulations. Adequate ventilation must be provided in enclosed / confined areas such as pits, shafts etc.

Non-warranty. The information contained herein is believed to be reliable to the best of our knowledge. However, all recommendations are made without guarantee of performance and with warranty of freedom from legal responsibility including patent liability on the part of Act (Thailand) Co., Ltd