Hydrapox FL04

Epoxy Enamel
Glossy Finish

Product Code : 5AC7

Description

Hydrapox FL04 is an epoxy enamel specially use for coating on wall and floor coating.

Advantage

- Good Adhesion to Substrate
- Easy to Clean
- Good Chemical resistance
- Good Durability
- Non-Toxic
- Easy to Apply and Maintain

Instruction for Use

1. Clean the substrate by remove laitance, oil, grease and dust.
2. Mix the resin with hardener at the ration 4:1 by wt. Stir it 2-3 min. with low speed mixer until homogeneous.
3. Apply by roller, brush or spray gun.

Packaging

Part A : 20 kg. , Part B : 5 kg.

Storage

Store in dry place at the room temperature.

Characteristic

Density	: 1.05±0.01
Solid Content	: 70 ± 2 %
Mixing Ratio	: 4 - 1 by Wt.
No. of Coat	: 2
Coverage	: 0.1-0.15 kg/ m^2
Thickness ,wet	: 100 - 150 µm.
,dry	: 60 - 90 µm.
Pot Life	: 30 -45 min.
Drying Time	: 3 Hr.
Time to recoat	: 16-24 Hr.

Cleaning

The equipment can be clean with Xylene immediately after use.

Precautions

During application observe safety hints on containers as well as local regulations. Adequate ventilation must be provided in enclosed / confined areas such as pits, shafts etc. In a liquid state the product and the thinner contaminate water and should not be poured into drains, water and ground.

Act (Thailand) Co., Ltd.
Address : 19 Moo 1 Kubangluang
Lardlumkaew Pathumthai 12140
Tel. : (66)-0-2979-4446-9 , (66)-0-29794936-9
Fax. : (66)-0-2979-4445
Email : info@actthai.com
Web Site : http://www.actthai.com

Non-warranty. The information contained herein is believed to be reliable to the best of our knowledge. However, all recommendations are made without guarantee of performance and with warranty of freedom from legal responsibility including patent liability on the part of Act (Thailand) Co., Ltd