



## *Hydrafoam PU-B*

### *Catalyst of Polyurethane foam Injection*

#### **Description**

Catalyst of Polyurethane foam (also available form ACT in the name of “Hydrafoam PU ”)

#### **Dosage**

3-5 % of PU Foam by weight

#### **Characteristic**

Form	: Liquid
Color	: Yellowish
Odor	: Nearly odorless
Setting Point	: Approx -40°C
Initial Boiling Point	: > 300°C
Density	: Approx 1.0 g./cc. at 20°C
Vapor Pressure	: < 10 mbar at 20°C
Viscosity	: Approx 140 mPa.s
Solubility in Water	: Insoluble
Flash Point	: Approx 288°C
Ignition Temperature	: Approx 380°C

#### **Storage**

Hydrafoam-PU must be stored in air tight containers.

#### **Packing**

1 L., 5 L.

#### **Act (Thailand) Co., Ltd.**

Address : 19 Moo 1 Kubangluang  
Lardlumkaew Pathumthai 12140  
Tel. : (66)-0-2979-4446-9 , (66)-0-29794936-9  
Fax. : (66)-0-2979-4445  
Email : [info@actthai.com](mailto:info@actthai.com)  
Web Site : <http://www.actthai.com>

Non-warranty. The information contained herein is believed to be reliable to the best of our knowledge. However, all recommendations are made without guarantee of performance and with warranty of freedom from legal responsibility including patent liability on the part of Act (Thailand) Co., Ltd