



Hydrapox FL-Primer

Fast Dry Epoxy Primer

Description

Hydrapox FL-Primer is a fast dry epoxy solvent base with excellent adhesion.

Object

- Use as a primer on the epoxy flooring system
- Improve adhesion between substrate and top coat.

Advantage

- Fast Dry
- Quick and Easy to Apply
- Good Chemical Resistance
- Good Adhesion on Damp Surface

Instruction for Use

- The surfaces to be coated should be dry, clean, free from loose materials, other contaminations as well as free from oils and fats.
- Mix Part A and Part B at the ratio 1:1 by wt. and mix it with low speed mixer around 3 min. until homogenous
- Apply to the substrate with roller.

Packaging

10 Kg./Set.

Characteristic

Mixing ratio :	1 / 1 By Wt.
Solid Content :	50 %
Density :	1.0
Bonding Strength :	More than concrete
Appearance :	Reddish
Drying Time :	2 Hr.
Curing Time :	4 Hr.
Thickness, Wet :	100 micron
, Dry :	50 micron

Storage

In unopened packs, Hydrapox FL-Primer has a shelf life of at least 12 months when stored in warehouse conditions below 35° C. It should, however not be stored at very low temperatures, to guarantee a good working consistency.

Cleaning

The working equipment, tools etc., can be mechanically cleaned by using brushes in combination with Xylene. The cleaning should be done immediately after the completion of the work and within the pot life of the material to avoid sediments on the equipments, tools etc.

Act (Thailand) Co., Ltd.

Address : 19 Moo 1 Kubangluang

Lardlumkaew Pathumthai 12140

Tel. : (66)-0-2979-4446-9 , (66)-0-29794936-9

Fax. : (66)-0-2979-4445

Email : info@actthai.com

Web Site : <http://www.actthai.com>

Non-warranty. The information contained herein is believed to be reliable to the best of our knowledge. However, all recommendations are made without guarantee of performance and with warranty of freedom from legal responsibility including patent liability on the part of Act (Thailand) Co., Ltd