



## *Polyflex RM*

*PU Middle Coat for Roof*

### **Description**

Polyflex RM is a two component polyurethane resin with special hardener.

### **Object**

Polyflex RM is use as a middle coat of PU waterproof coating system on roof, concrete, wood etc.

### **Advantage**

- Strongly adhesion property
- Easy to apply
- Excellent whether and chemical resistance
- Extend the aging of concrete, cement and steel material

### **Characteristic**

● Density :	1.30 ± 0.05 kg./L.
● Hardness :	20-40 Shore A
● Standard Applying :	2.5 – 2.8 kg./m <sup>2</sup>
● Thickness :	2 mm.
● Mixing Ratio :	A : B = 3 : 1 by Wt.
● Applying Time (25°C) :	60 – 80 min.
● Drying Time (25°C) :	24 Hr.
● Applying Method :	By Trowel

### **Packaging**

30 Kg./Set.

### **Storage**

In unopened packs, Polyflex RM has a shelf life of at least 12 months when stored in warehouse conditions below 35 °C. It should, however not be stored at very low temperatures, to guarantee a good working consistency.

### **Act (Thailand) Co., Ltd.**

Address : 19 Moo 1 Kubangluang

Lardlumkaew Pathumthai 12140

Tel. : (66)-0-2979-4446-9 , (66)-0-29794936-9

Fax. : (66)-0-2979-4445

Email : [info@actthai.com](mailto:info@actthai.com)

Web Site : <http://www.actthai.com>

Non-warranty. The information contained herein is believed to be reliable to the best of our knowledge. However, all recommendations are made without guarantee of performance and with warranty of freedom from legal responsibility including patent liability on the part of Act (Thailand) Co., Ltd

