



Polyflex RT

PU Top Coat for Roof

Description

Polyflex RT is a two component polyurethane resin with special hardener.

Object

Polyflex RT is use as a top coat of PU waterproof coating system on roof, concrete, wood etc.

Advantage

- Excellent adaptation on weather effects
- Excellent adhesion property
- Excellent chemical resistance
- Abrasion resistance and excellent compressive strength

Characteristic

● Solid :	55 - 60 %
● Viscosity :	65 - 85 KU
● Standard Applying :	0.25 - 0.35 kg./m ²
● Mixing Ratio :	A : B = 1 : 1 by Wt.
● Applying Time (25°C) :	60 – 80 min.
● Drying Time (25°C)	
Contacting Time :	2 Hrs.
Consolidating Time :	4-6 Hrs.
Completely Hardened :	7 Days.
● Applying Method :	By Brush or Roller

Packaging

20 Kgs./Set.

Storage

In unopened packs, Polyflex RT has a shelf life of at least 12 months when stored in warehouse conditions below 35 °C. It should, however not be stored at very low temperatures, to guarantee a good working consistency.

Act (Thailand) Co., Ltd.

Address : 19 Moo 1 Kubangluang

Lardlumkaew Pathumthai 12140

Tel. : (66)-0-2979-4446-9 , (66)-0-29794936-9

Fax. : (66)-0-2979-4445

Email : info@actthai.com

Web Site : <http://www.actthai.com>

Non-warranty. The information contained herein is believed to be reliable to the best of our knowledge. However, all recommendations are made without guarantee of performance and with warranty of freedom from legal responsibility including patent liability on the part of Act (Thailand) Co., Ltd