



## *Primer MB*

### *Bituminous Primer for Waterproofing Sheet*

#### **Description**

Primer MB is a solvent base, black asphalt liquid made of refined bitumen in quick evaporating solvent specially designed to deeply penetrate and seal porous surfaces to provide a base for waterproofing membranes.

#### **Object**

Primer MB is used to seal and prepare base surfaces such as concrete, brickwork, metal and existing bituminous roofing, ensuring that a good bond is achieved with hot bitumen, torch-on membranes or cold adhesives.

#### **Advantage**

- Deeply penetrate to make good adhesion
- Not necessary to heat
- Economical and easy to apply
- Quick Dry

#### **Instruction for Use**

- The surfaces should be dry, clean, free from loose materials, other contaminations as well as free from oils and fats.
- Apply with a paint brush, roller or spray equipment. Try to cover the surface completely.

#### **Coverage**

8 – 10 m<sup>2</sup>/L.

#### **Act (Thailand) Co., Ltd.**

Address : 19 Moo 1 Kubangluang

Lardlumkaew Pathumthai 12140

Tel. : (66)-0-2979-4446-9 , (66)-0-29794936-9

Fax. : (66)-0-2979-4445

Email : [info@actthai.com](mailto:info@actthai.com)

Web Site : <http://www.actthai.com>

#### **Instruction for Use**

- The surfaces should be dry, clean, free from loose materials, other contaminations as well as free from oils and fats.
- Apply with a paint brush, roller or spray equipment. Try to cover the surface completely.
- Allow to dry for 1-2 Hr. before applying with another sealing.

#### **Characteristics**

Specific Gravity :	0.92-0.97
Drying Time :	1-2 Hr.
Solid Content	50 %

#### **Packaging**

20 L./Pail

#### **Cleaning**

The working equipment, tools etc., can be mechanically cleaned by using brushes in combination with Xylene.

#### **Storage**

In unopened packs, Primer MB has a shelf life of at least 12 months when stored in warehouse conditions below 35 ° C. It should, however, not be stored at very low temperatures, to guarantee a good working consistency.

Non-warranty. The information contained herein is believed to be reliable to the best of our knowledge. However, all recommendations are made without guarantee of performance and with warranty of freedom from legal responsibility including patent liability on the part of Act (Thailand) Co., Ltd.